

MATCRETE

DIAMOND FINISH

MAINTENANCE WAX

Matcrete **DIAMOND FINISH** Maintenance Wax is a high performance interior/exterior acrylic polish manufactured specifically for maintaining previously sealed masonry surfaces. Diamond Finish is formulated to enhance and provide for additional scuff resistance and protection to the pre-sealed surface. Diamond Finish will add exceptional resistance to dirt retention. Sealed surfaces periodically maintained with Diamond Finish, will retain their original sealed appearance longer. Diamond Finish is not recommended for concrete garage floors or other surfaces where vehicles are parked.

PACKAGE SIZES/COVERAGE

- 1 gallon of Diamond Finish covers 500-1000 square feet depending on the surface porosity.
- 5 gallons of Diamond Finish covers 2500-5000 square feet depending on the surface porosity.
- Also available in 55 gallon drums.

PREPARATION

Surfaces must be clean, free of grease, oil, dirt, wax, polish or foreign matter. Make certain that the bond to any previously applied coating is secure by applying Diamond Finish to a small area and check for possible lifting before proceeding. On newly sealed surfaces, allow 24-48 hours for sealer to cure before applying.

METHOD OF APPLICATION

Surface temperature should be between 55°F and 80°F. Gently shake contents before use. After thorough preparation of surfaces, Diamond Finish can be applied by using a fine textured sponge or brush. Apply as is. Do not dilute. One application, over a sufficiently sealed surface, is generally required. An additional application may be required depending upon the surface's porosity after sealing. High traffic area will require more frequent applications to maintain their high luster appearance. Allow 2-3 hours between applications and allow 2-3 hours before using the finished surface. Longer drying time will be necessary during cool and humid conditions.

PRECAUTIONS

Do not allow Diamond Finish to freeze. If allowed to freeze, material will not thaw to a usable product.

CLEANING OF TOOLS

Tools and hands may be cleaned with mild liquid detergent and warm water. Dry material can be removed with Acetone following the manufacturer's cautions. Disposal of any unused material, if desired, must comply with Local, State and Federal regulations.

WARNING! POSSIBLE SLIPPERINESS

Diamond Finish, like any good finish, reduces the porosity of the surface being sealed. Be aware that oil, water, mud, or other materials on a sealed walkway can make the surface slippery and therefore potentially dangerous. Good housekeeping and maintenance are important; good drainage is imperative.

TECHNICAL BULLETIN

DIAMOND FINISH-02/06

MATCRETE · 1495 Hudson Avenue · Ontario, CA · 91764
PHONE (800)777-7063 · FAX (909)635-0165
www.matcrete.com